

# SAFETY DATA SHEET

9327

## Section 1. Identification

**Product name** : KRYLON® OUTDOOR DECOR  
Satin Dahlia

**Product code** : 9327

**Other means of identification** : Not available.

**CAS #** : Not applicable.

**Product type** : Aerosol.

**Relevant identified uses of the substance or mixture and uses advised against**

Not applicable.

**Manufacturer** : Krylon Products Group  
101 Prospect Avenue NW  
Cleveland, OH 44115

**Emergency telephone number of the company** : US / Canada: (216) 566-2917  
Mexico: SETIQ 01-800-00-214-00 / D.F. 5559-1588 24 hours / 365 days a year

**Product Information Telephone Number** : US / Canada: (800) 457-9566  
Mexico: Not Available

**Regulatory Information Telephone Number** : US / Canada: (216) 566-2902  
Mexico: Not Available

**Transportation Emergency Telephone Number** : US / Canada: (800) 424-9300  
Mexico: SETIQ 01-800-00-214-00 / D.F. 5559-1588 24 hours / 365 days a year

## Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 1  
GASES UNDER PRESSURE - Compressed gas  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 1  
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 39.3%  
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 67.2%  
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 71.5%

### GHS label elements

**Date of issue/Date of revision** : 7/6/2017      **Date of previous issue** : 6/6/2017      **Version** : 9      1/18

## Section 2. Hazards identification

### Hazard pictograms



### Signal word

: Danger

### Hazard statements

: Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Suspected of causing cancer.  
May be fatal if swallowed and enters airways.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Causes damage to organs through prolonged or repeated exposure. (lungs)

### Precautionary statements

#### General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

#### Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Pressurized container: Do not pierce or burn, even after use.

#### Response

: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

#### Storage

: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

#### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

#### Hazards not otherwise classified

: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Other means of identification** : Not available.

### CAS number/other identifiers

<b>Ingredient name</b>	<b>% by weight</b>	<b>CAS number</b>
Acetone	23.91	67-64-1
Propane	20.4	74-98-6
n-Butyl Acetate	12.35	123-86-4
Butane	9.6	106-97-8
Lt. Aliphatic Hydrocarbon Solvent	7.24	64742-89-8
Ethyl 3-Ethoxypropionate	4	763-69-9
Talc	2.3	14807-96-6
Titanium Dioxide	2.07	13463-67-7
1-Methoxy-2-Propanol Acetate	1.5	108-65-6
Xylene	1.5	1330-20-7
Barium Sulfate	1.07	7727-43-7
Ethylbenzene	0.4	100-41-4
Unsaturated Fatty Acids	0.17	85711-46-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Date of issue/Date of revision** : 7/6/2017      **Date of previous issue** : 6/6/2017      **Version** : 9      3/18

## Section 4. First aid measures

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### Specific hazards arising from the chemical

- : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

### Hazardous thermal decomposition products

- : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides  
metal oxide/oxides

## Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

## Section 7. Handling and storage

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
Acetone	<b>ACGIH TLV (United States, 3/2016).</b> TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. <b>NIOSH REL (United States, 10/2016).</b> TWA: 250 ppm 10 hours. TWA: 590 mg/m <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 6/2016).</b> TWA: 1000 ppm 8 hours. TWA: 2400 mg/m <sup>3</sup> 8 hours.
Propane	<b>NIOSH REL (United States, 10/2016).</b> TWA: 1000 ppm 10 hours. TWA: 1800 mg/m <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 6/2016).</b> TWA: 1000 ppm 8 hours. TWA: 1800 mg/m <sup>3</sup> 8 hours.
n-Butyl Acetate	<b>NIOSH REL (United States, 10/2016).</b> TWA: 150 ppm 10 hours. TWA: 710 mg/m <sup>3</sup> 10 hours. STEL: 200 ppm 15 minutes. STEL: 950 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL (United States, 6/2016).</b> TWA: 150 ppm 8 hours. TWA: 710 mg/m <sup>3</sup> 8 hours. <b>ACGIH TLV (United States, 3/2016).</b> STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours.
Butane	<b>NIOSH REL (United States, 10/2016).</b> TWA: 800 ppm 10 hours. TWA: 1900 mg/m <sup>3</sup> 10 hours. <b>ACGIH TLV (United States, 3/2016).</b> STEL: 1000 ppm 15 minutes.
Lt. Aliphatic Hydrocarbon Solvent	None.
Ethyl 3-Ethoxypropionate	None.
Talc	<b>NIOSH REL (United States, 10/2016).</b> TWA: 2 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction <b>ACGIH TLV (United States, 3/2016).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction
Titanium Dioxide	<b>ACGIH TLV (United States, 3/2016).</b> TWA: 10 mg/m <sup>3</sup> 8 hours.

## Section 8. Exposure controls/personal protection

<p>1-Methoxy-2-Propanol Acetate</p> <p>Xylene</p>	<p><b>OSHA PEL (United States, 6/2016).</b> TWA: 15 mg/m<sup>3</sup> 8 hours. Form: Total dust</p> <p><b>AIHA WEEL (United States, 10/2011).</b> TWA: 50 ppm 8 hours.</p> <p><b>ACGIH TLV (United States, 3/2016).</b> TWA: 100 ppm 8 hours. TWA: 434 mg/m<sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 6/2016).</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.</p>
<p>Barium Sulfate</p>	<p><b>ACGIH TLV (United States, 3/2016).</b> TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction</p> <p><b>NIOSH REL (United States, 10/2016).</b> TWA: 5 mg/m<sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m<sup>3</sup> 10 hours. Form: Total</p> <p><b>OSHA PEL (United States, 6/2016).</b> TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m<sup>3</sup> 8 hours. Form: Total dust</p>
<p>Ethylbenzene</p>	<p><b>ACGIH TLV (United States, 3/2016).</b> TWA: 20 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2016).</b> TWA: 100 ppm 10 hours. TWA: 435 mg/m<sup>3</sup> 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 6/2016).</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.</p>
<p>Unsaturated Fatty Acids</p>	<p>None.</p>

### Occupational exposure limits (Canada)

Ingredient name	Exposure limits
<p>Acetone</p>	<p><b>CA Alberta Provincial (Canada, 4/2009).</b> 8 hrs OEL: 1200 mg/m<sup>3</sup> 8 hours. 15 min OEL: 1800 mg/m<sup>3</sup> 15 minutes. 8 hrs OEL: 500 ppm 8 hours. 15 min OEL: 750 ppm 15 minutes.</p> <p><b>CA British Columbia Provincial (Canada, 7/2016).</b> TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes.</p> <p><b>CA Ontario Provincial (Canada, 7/2015).</b> TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.</p> <p><b>CA Québec Provincial (Canada, 1/2014).</b> TWA<sub>EV</sub>: 500 ppm 8 hours. TWA<sub>EV</sub>: 1190 mg/m<sup>3</sup> 8 hours. STEV: 1000 ppm 15 minutes. STEV: 2380 mg/m<sup>3</sup> 15 minutes.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b> STEL: 750 ppm 15 minutes. TWA: 500 ppm 8 hours.</p>

## Section 8. Exposure controls/personal protection

Propane

**CA Alberta Provincial (Canada, 4/2009).**  
8 hrs OEL: 1000 ppm 8 hours.  
**CA British Columbia Provincial (Canada, 7/2016).**  
TWA: 1000 ppm 8 hours.  
**CA Québec Provincial (Canada, 1/2014).**  
TWA: 1000 ppm 8 hours.  
TWA: 1800 mg/m<sup>3</sup> 8 hours.  
**CA Ontario Provincial (Canada, 7/2015).**  
TWA: 1000 ppm 8 hours.  
**CA Saskatchewan Provincial (Canada, 7/2013).**  
STEL: 1250 ppm 15 minutes.  
TWA: 1000 ppm 8 hours.

n-Butyl Acetate

**CA Alberta Provincial (Canada, 4/2009).**  
15 min OEL: 200 ppm 15 minutes.  
15 min OEL: 950 mg/m<sup>3</sup> 15 minutes.  
8 hrs OEL: 150 ppm 8 hours.  
8 hrs OEL: 713 mg/m<sup>3</sup> 8 hours.  
**CA British Columbia Provincial (Canada, 7/2016).**  
TWA: 20 ppm 8 hours.  
**CA Ontario Provincial (Canada, 7/2015).**  
TWA: 150 ppm 8 hours.  
STEL: 200 ppm 15 minutes.  
**CA Québec Provincial (Canada, 1/2014).**  
TWA: 150 ppm 8 hours.  
TWA: 713 mg/m<sup>3</sup> 8 hours.  
STEL: 200 ppm 15 minutes.  
STEL: 950 mg/m<sup>3</sup> 15 minutes.  
**CA Saskatchewan Provincial (Canada, 7/2013).**  
STEL: 200 ppm 15 minutes.  
TWA: 150 ppm 8 hours.

Butane

**CA Alberta Provincial (Canada, 4/2009).**  
8 hrs OEL: 1000 ppm 8 hours.  
**CA British Columbia Provincial (Canada, 7/2016).**  
TWA: 600 ppm 8 hours.  
STEL: 750 ppm 15 minutes.  
**CA Québec Provincial (Canada, 1/2014).**  
TWA: 800 ppm 8 hours.  
TWA: 1900 mg/m<sup>3</sup> 8 hours.  
**CA Ontario Provincial (Canada, 7/2015).**  
TWA: 800 ppm 8 hours.  
**CA Saskatchewan Provincial (Canada, 7/2013).**  
STEL: 1250 ppm 15 minutes.  
TWA: 1000 ppm 8 hours.

Xylene

**CA Alberta Provincial (Canada, 4/2009).**  
8 hrs OEL: 100 ppm 8 hours.  
15 min OEL: 651 mg/m<sup>3</sup> 15 minutes.  
15 min OEL: 150 ppm 15 minutes.  
8 hrs OEL: 434 mg/m<sup>3</sup> 8 hours.  
**CA British Columbia Provincial (Canada, 7/2016).**  
TWA: 100 ppm 8 hours.  
STEL: 150 ppm 15 minutes.



## Section 8. Exposure controls/personal protection

Ethylbenzene	<p><b>CA Québec Provincial (Canada, 1/2014).</b>            TWAEV: 100 ppm 8 hours.            TWAEV: 434 mg/m<sup>3</sup> 8 hours.            STEV: 150 ppm 15 minutes.            STEV: 651 mg/m<sup>3</sup> 15 minutes.</p> <p><b>CA Ontario Provincial (Canada, 7/2015).</b>            STEL: 150 ppm 15 minutes.            TWA: 100 ppm 8 hours.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b>            STEL: 150 ppm 15 minutes.            TWA: 100 ppm 8 hours.</p> <p><b>CA Alberta Provincial (Canada, 4/2009).</b>            8 hrs OEL: 100 ppm 8 hours.            8 hrs OEL: 434 mg/m<sup>3</sup> 8 hours.            15 min OEL: 543 mg/m<sup>3</sup> 15 minutes.            15 min OEL: 125 ppm 15 minutes.</p> <p><b>CA British Columbia Provincial (Canada, 7/2016).</b>            TWA: 20 ppm 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 7/2015).</b>            TWA: 20 ppm 8 hours.</p> <p><b>CA Québec Provincial (Canada, 1/2014).</b>            TWAEV: 100 ppm 8 hours.            TWAEV: 434 mg/m<sup>3</sup> 8 hours.            STEV: 125 ppm 15 minutes.            STEV: 543 mg/m<sup>3</sup> 15 minutes.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b>            STEL: 125 ppm 15 minutes.            TWA: 100 ppm 8 hours.</p>
--------------	--

### Occupational exposure limits (Mexico)

Ingredient name	Exposure limits
Acetone	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.
Propane	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 1000 ppm 8 hours.
n-Butyl Acetate	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.
Butane	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 1000 ppm 8 hours.
Xylene	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
Ethylbenzene	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 20 ppm 8 hours.

### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Section 8. Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

**Physical state** : Liquid.  
**Color** : Not available.  
**Odor** : Not available.  
**Odor threshold** : Not available.  
**pH** : 7  
**Melting point** : Not available.  
**Boiling point** : Not available.  
**Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]  
**Evaporation rate** : 5.6 (butyl acetate = 1)  
**Flammability (solid, gas)** : Not available.  
**Lower and upper explosive (flammable) limits** : Lower: 0.9%  
Upper: 13.1%  
**Vapor pressure** : 101.3 kPa (760 mm Hg) [at 20°C]  
**Vapor density** : 1.55 [Air = 1]

## Section 9. Physical and chemical properties

Relative density	: 0.75
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): <0.205 cm <sup>2</sup> /s (<20.5 cSt)
Molecular weight	: Not applicable.
<b>Aerosol product</b>	
Type of aerosol	: Spray
Heat of combustion	: 28.554 kJ/g

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetone	LD50 Oral	Rat	5800 mg/kg	-
n-Butyl Acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m <sup>3</sup>	4 hours
Ethyl 3-Ethoxypropionate	LD50 Oral	Rat	3200 mg/kg	-
1-Methoxy-2-Propanol Acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
Xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

#### Irritation/Corrosion

## Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetone	Eyes - Mild irritant	Human	-	186300 parts per million	-
	Eyes - Mild irritant	Rabbit	-	10 microliters	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
n-Butyl Acetate	Skin - Mild irritant	Rabbit	-	395 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
Ethyl 3-Ethoxypropionate	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Talc	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
Xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Ethylbenzene	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
Talc	-	3	-
Titanium Dioxide	-	2B	-
Xylene	-	3	-
Ethylbenzene	-	2B	-

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Acetone	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Propane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
n-Butyl Acetate	Category 3	Not applicable.	Narcotic effects
Butane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Lt. Aliphatic Hydrocarbon Solvent	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Xylene	Category 3	Not applicable.	Respiratory tract irritation
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Acetone	Category 2	Not determined	Not determined
Propane	Category 2	Not determined	Not determined
Butane	Category 2	Not determined	Not determined
Lt. Aliphatic Hydrocarbon Solvent	Category 2	Not determined	Not determined
Talc	Category 1	Inhalation	lungs
Xylene	Category 2	Not determined	Not determined
Ethylbenzene	Category 2	Not determined	Not determined

### Aspiration hazard

Name	Result
Propane	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Xylene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness

- Inhalation** : Adverse symptoms may include the following:  
 respiratory tract irritation  
 coughing  
 nausea or vomiting  
 headache  
 drowsiness/fatigue  
 dizziness/vertigo  
 unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness
- Ingestion** : Adverse symptoms may include the following:  
 nausea or vomiting

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

**Long term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

**Potential chronic health effects**

Not available.

- General** : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

**Numerical measures of toxicity**

**Acute toxicity estimates**

<b>Route</b>	<b>ATE value</b>
Oral	37972.9 mg/kg
Dermal	24074.7 mg/kg
Inhalation (gases)	95235.5 ppm

**Section 12. Ecological information**

**Toxicity**

## Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Acetone	Acute EC50 7200000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 6900 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.1 mg/l Fresh water	Fish - Fundulus heteroclitus	4 weeks
n-Butyl Acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Lt. Aliphatic Hydrocarbon Solvent	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 8500 µg/l Marine water	Fish - Pimephales promelas	96 hours
Barium Sulfate	Acute LC50 13400 µg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute EC50 634 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
Ethylbenzene	Acute EC50 32000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 3600 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 6530 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 2930 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 4200 µg/l Fresh water		

### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetone	-	-	Readily
n-Butyl Acetate	-	-	Readily
Xylene	-	-	Readily
Ethylbenzene	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Xylene	-	8.1 to 25.9	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.






**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

	<b>DOT Classification</b>	<b>TDG Classification</b>	<b>Mexico Classification</b>	<b>IATA</b>	<b>IMDG</b>
<b>UN number</b>	UN1950	UN1950	UN1950	UN1950	UN1950
<b>UN proper shipping name</b>	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
<b>Transport hazard class(es)</b>	2.1 	2.1 	2.1 	2.1 	2.1 
<b>Packing group</b>	-	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.	No.
<b>Additional information</b>	-  <b>ERG No.</b> 126	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).  <b>ERG No.</b> 126	-  <b>ERG No.</b> 126	-	<b>Emergency schedules</b> F-D, S-U

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

**Proper shipping name** : Not available.  
**Ship type** : Not available.  
**Pollution category** : Not available.



## Section 15. Regulatory information

### [SARA 313](#)

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

### [California Prop. 65](#)

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## Section 16. Other information

### [Hazardous Material Information System \(U.S.A.\)](#)

Health	*	2
Flammability		3
Physical hazards		0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### [Procedure used to derive the classification](#)

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 1	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

### [History](#)

Date of printing : 7/6/2017

Date of issue/Date of revision : 7/6/2017

Date of previous issue : 6/6/2017

Version : 9

Key to abbreviations : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

### [Notice to reader](#)

## Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.