

SAFETY DATA SHEET

69322

Section 1. Identification

Product name : KRYLON® RUST PROTECTOR™ Hammered Finish (Aerosol)
Charcoal Gray

Product code : 69322

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Krylon Products Group
101 W. Prospect Avenue
Cleveland, OH 44115

Emergency telephone number of the company : US / Canada: (216) 566-2917
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Product Information Telephone Number : US / Canada: (800) 457-9566
Mexico: Not Available

Regulatory Information Telephone Number : US / Canada: (216) 566-2902
Mexico: Not Available

Transportation Emergency Telephone Number : US / Canada: (216) 566-2917
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 28.1% (oral), 28.1% (dermal), 28.1% (inhalation)

GHS label elements

Hazard pictograms :



Signal word : Danger

Date of issue/Date of revision : 4/13/2021 **Date of previous issue** : 2/4/2021

Version : 15 1/18

69322 KRYLON® RUST PROTECTOR™ Hammered Finish (Aerosol)
Charcoal Gray

SHW-85-NA-GHS-US

Section 2. Hazards identification

- Hazard statements** : Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 Causes serious eye irritation.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements**
- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.
- Response** : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
 Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
- Hazards not otherwise classified** : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.
- CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Acetone	≥25 - ≤50	67-64-1
Propane	≥10 - ≤25	74-98-6
Lt. Aliphatic Hydrocarbon Solvent	≥10 - ≤25	64742-89-8
Ethylbenzene	≤5	100-41-4
Xylene, mixed isomers	≤3	1330-20-7
Hydrotreated Heavy Petroleum Naphtha	≤0.3	64742-48-9
Light Aromatic Hydrocarbons	≤0.3	64742-95-6
Zirconium 2-Ethylhexanoate	≤0.3	22464-99-9

Section 3. Composition/information on ingredients

Carbon Black	≤0.3	1333-86-4
Hydrotreated Heavy Petroleum Naphtha	≤0.3	64742-48-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Section 4. First aid measures

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Acetone	67-64-1	ACGIH TLV (United States, 3/2020). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. NIOSH REL (United States, 10/2016). TWA: 250 ppm 10 hours. TWA: 590 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m ³ 8 hours.
Propane	74-98-6	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2020). Oxygen Depletion [Asphyxiant]. Explosive potential. None.
Lt. Aliphatic Hydrocarbon Solvent Ethylbenzene	64742-89-8 100-41-4	ACGIH TLV (United States, 3/2020). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Xylene, mixed isomers	1330-20-7	ACGIH TLV (United States, 3/2020). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Hydrotreated Heavy Petroleum Naphtha Light Aromatic Hydrocarbons Zirconium 2-Ethylhexanoate	64742-48-9 64742-95-6 22464-99-9	None. None. ACGIH TLV (United States, 3/2020). TWA: 5 mg/m ³ , (as Zr) 8 hours. STEL: 10 mg/m ³ , (as Zr) 15 minutes. NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ , (as Zr) 10 hours. STEL: 10 mg/m ³ , (as Zr) 15 minutes. OSHA PEL (United States, 5/2018).

Section 8. Exposure controls/personal protection

Carbon Black	1333-86-4	TWA: 5 mg/m ³ , (as Zr) 8 hours. ACGIH TLV (United States, 3/2020). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 3.5 mg/m ³ 10 hours. TWA: 0.1 mg of PAHs/cm ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m ³ 8 hours.
Hydrotreated Heavy Petroleum Naptha	64742-48-9	None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
acetone	67-64-1	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1200 mg/m ³ 8 hours. 15 min OEL: 1800 mg/m ³ 15 minutes. 8 hrs OEL: 500 ppm 8 hours. 15 min OEL: 750 ppm 15 minutes. CA British Columbia Provincial (Canada, 1/2020). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Quebec Provincial (Canada, 7/2019). TWAEV: 500 ppm 8 hours. TWAEV: 1190 mg/m ³ 8 hours. STEV: 1000 ppm 15 minutes. STEV: 2380 mg/m ³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 750 ppm 15 minutes. TWA: 500 ppm 8 hours.
Normal propane	74-98-6	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 1/2020). Oxygen Depletion [Asphyxiant]. Explosive potential. CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.
Ethylbenzene	100-41-4	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 100 ppm 8 hours. 8 hrs OEL: 434 mg/m ³ 8 hours. 15 min OEL: 543 mg/m ³ 15 minutes. 15 min OEL: 125 ppm 15 minutes. CA British Columbia Provincial (Canada,

Section 8. Exposure controls/personal protection

Xylene	1330-20-7	<p>1/2020). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 100 ppm 8 hours. TWAEV: 434 mg/m³ 8 hours. STEV: 125 ppm 15 minutes. STEV: 543 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 100 ppm 8 hours. 15 min OEL: 651 mg/m³ 15 minutes. 15 min OEL: 150 ppm 15 minutes. 8 hrs OEL: 434 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 1/2020). TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. CA Quebec Provincial (Canada, 7/2019). TWAEV: 100 ppm 8 hours. TWAEV: 434 mg/m³ 8 hours. STEV: 150 ppm 15 minutes. STEV: 651 mg/m³ 15 minutes. CA Ontario Provincial (Canada, 6/2019). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.</p>
Methyl alcohol	67-56-1	<p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 262 mg/m³ 8 hours. 8 hrs OEL: 200 ppm 8 hours. 15 min OEL: 250 ppm 15 minutes. 15 min OEL: 328 mg/m³ 15 minutes. CA British Columbia Provincial (Canada, 1/2020). Absorbed through skin. TWA: 200 ppm 8 hours. STEL: 250 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). Absorbed through skin. TWA: 200 ppm 8 hours. STEL: 250 ppm 15 minutes. CA Quebec Provincial (Canada, 7/2019). Absorbed through skin. TWAEV: 200 ppm 8 hours. TWAEV: 262 mg/m³ 8 hours. STEV: 250 ppm 15 minutes. STEV: 328 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 250 ppm 15 minutes.</p>

Section 8. Exposure controls/personal protection

Zirconium 2-Ethylhexanoate	22464-99-9	<p>TWA: 200 ppm 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 5 mg/m³, (as Zr) 8 hours. 15 min OEL: 10 mg/m³, (as Zr) 15 minutes. CA British Columbia Provincial (Canada, 1/2020). TWA: 5 mg/m³, (as Zr) 8 hours. STEL: 10 mg/m³, (as Zr) 15 minutes. CA Quebec Provincial (Canada, 7/2019). TWAEV: 5 mg/m³, (as Zr) 8 hours. STEV: 10 mg/m³, (as Zr) 15 minutes. CA Ontario Provincial (Canada, 6/2019). STEL: 10 mg/m³, (as Zr) 15 minutes. TWA: 5 mg/m³, (as Zr) 8 hours.</p>
Carbon black	1333-86-4	<p>CA British Columbia Provincial (Canada, 1/2020). TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.</p>

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
Acetone	67-64-1	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.
Propane	74-98-6	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Ethylbenzene	100-41-4	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Xylene, mixed isomers	1330-20-7	NOM-010-STPS-2014 (Mexico, 4/2016). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
Zirconium 2-Ethylhexanoate	22464-99-9	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 5 mg/m ³ , (as Zr) 8 hours. STEL: 10 mg/m ³ , (as Zr) 15 minutes.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 7
- Melting point/freezing point** : Not available.
- Boiling point/boiling range** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 5.6 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 0.9%
Upper: 12.8%
- Vapor pressure** : 101.3 kPa (760 mm Hg) [at 20°C]
- Vapor density** : 1.55 [Air = 1]
- Relative density** : 0.78
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.

Section 9. Physical and chemical properties

- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
- Molecular weight** : Not applicable.
- Aerosol product**
 - Type of aerosol** : Spray
 - Heat of combustion** : 25.569 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetone	LD50 Oral	Rat	5800 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
Xylene, mixed isomers	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Hydrotreated Heavy Petroleum Naphtha	LC50 Inhalation Vapor	Rat	8500 mg/m ³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
Light Aromatic Hydrocarbons	LD50 Oral	Rat	8400 mg/kg	-
Zirconium 2-Ethylhexanoate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-
Hydrotreated Heavy Petroleum Naphtha	LC50 Inhalation Vapor	Rat	8500 mg/m ³	4 hours
	LD50 Oral	Rat	>6 g/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 uL	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
Ethylbenzene	Skin - Mild irritant	Rabbit	-	395 mg	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
Xylene, mixed isomers	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Light Aromatic Hydrocarbons	Skin - Moderate irritant	Rabbit	-	100 %	-
	Eyes - Mild irritant	Rabbit	-	24 hours 100 uL	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethylbenzene	-	2B	-
Xylene, mixed isomers	-	3	-
Carbon Black	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Acetone	Category 3	-	Respiratory tract irritation
Propane	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Lt. Aliphatic Hydrocarbon Solvent	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Ethylbenzene	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation

Section 11. Toxicological information

Xylene, mixed isomers	Category 3	-	Narcotic effects
	Category 3		Respiratory tract irritation
Hydrotreated Heavy Petroleum Naphtha Light Aromatic Hydrocarbons	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Hydrotreated Heavy Petroleum Naphtha	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Acetone	Category 2	-	-
Propane	Category 2	-	-
Lt. Aliphatic Hydrocarbon Solvent	Category 2	-	-
Ethylbenzene	Category 2	-	-
Xylene, mixed isomers	Category 2	-	-
Light Aromatic Hydrocarbons	Category 2	-	-
Hydrotreated Heavy Petroleum Naphtha	Category 2	-	-

Aspiration hazard

Name	Result
Propane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1
Hydrotreated Heavy Petroleum Naphtha	ASPIRATION HAZARD - Category 1
Light Aromatic Hydrocarbons	ASPIRATION HAZARD - Category 1
Hydrotreated Heavy Petroleum Naphtha	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness

Section 11. Toxicological information

reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Skin contact : Adverse symptoms may include the following:
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Ingestion : Adverse symptoms may include the following:
 nausea or vomiting
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	40228.82 mg/kg
Dermal	51159.31 mg/kg
Inhalation (gases)	311606.69 ppm
Inhalation (vapors)	158.27 mg/l

Section 12. Ecological information

Toxicity

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Acetone	Acute EC50 7200000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 4.42589 ml/L Marine water	Crustaceans - Acartia tonsa - Copepodid	48 hours
	Acute LC50 7460000 µg/l Fresh water	Daphnia - Daphnia cucullata	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
Lt. Aliphatic Hydrocarbon Solvent	Chronic NOEC 5 µg/l Marine water	Fish - Gasterosteus aculeatus - Larvae	42 days
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
Xylene, mixed isomers	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetone	-	-	Readily
Ethylbenzene	-	-	Readily
Xylene, mixed isomers	-	-	Readily
Light Aromatic Hydrocarbons	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Xylene, mixed isomers	-	8.1 to 25.9	low
Hydrotreated Heavy Petroleum Naphtha	-	10 to 2500	high
Light Aromatic Hydrocarbons	-	10 to 2500	high
Zirconium 2-Ethylhexanoate	-	2.96	low
Hydrotreated Heavy Petroleum Naphtha	-	10 to 2500	high

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	- ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	- Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Emergency schedules F-D, S-U Dependent upon container size, this product may ship under the Limited Quantity shipping exception.

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Section 14. Transport information

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

- International lists :
- Australia inventory (AIIIC): Not determined.
 - China inventory (IECSC): Not determined.
 - Japan inventory (CSCL): Not determined.
 - Japan inventory (ISHL): Not determined.
 - Korea inventory (KECI): Not determined.
 - New Zealand Inventory of Chemicals (NZIoC): Not determined.
 - Philippines inventory (PICCS): Not determined.
 - Taiwan Chemical Substances Inventory (TCSI): Not determined.
 - Thailand inventory: Not determined.
 - Turkey inventory: Not determined.
 - Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		4
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of issue/Date of revision : 4/13/2021	Date of previous issue : 2/4/2021	Version : 15	17/18
69322	KRYLON® RUST PROTECTOR™ Hammered Finish (Aerosol) Charcoal Gray	SHW-85-NA-GHS-US	

Section 16. Other information

Date of printing : 4/13/2021
Date of issue/Date of revision : 4/13/2021
Date of previous issue : 2/4/2021
Version : 15
Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

▣ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.